



CF5518 XTREME DUTY • 8YR LED 2' LINEAR HIGH BAY

HIGH-BAY LUMINAIRES FOR COMMERCIAL AND INDUSTRIAL BUILDINGS

FEATURES

- High lumen output bright and high lumen per watt.
- Integrated LED maintenance free.
- Replaces HID and fluorescent fixtures.
- Wide beam angle uniform light distribution.
- All steel surfaces are painted after fabrication for smooth edges and rounded corners.

MOUNTING

Designed for suspended or pendent mounting.

APPLICATION

Larger warehouses, retail applications, commercial buildings and work areas.

ELECTRICAL

CERTIFIED

Wattage	223W		
Voltage	347-480V		
Current	0.63A 0.9		
Power Factor			
Total Harmonic Distortion (THD)	10		
LIGHTING PERFORMANCE			
Lumens	29213		
Lumens Per Watt (LPW)	131		
Color Temperature (CCT)	5000K		
Color Rendering (CRI)	82		
R9 (Red Value)	7.2		
R13 (Skin Tones)	83		
Beam Angle	120°		
Light Distribution	Type VS		
BUG Rating (Backlight, Uplight, and Glare)	B4 - U0 - G2		
Dimmable Lighting Control	(Dimmable 0-10V, Range 10% - 100%		
ENVIRONMENT			
Operating Temperature	-4° ~ 122°F		
Suitable Location	DAMP		
Ingress Protection Rating	IP40		
LIFESPAN			
Average Life (Hours)	50,000		
Warranty (Years)	8		
COMPONENTS			
LED Light Source	Seoul		
Driver	VEL100240HVHDA (2 ea.)		
CONSTRUCTION			
Housing	24 Gauge C.R.S.		
Lens	Acrylic (PMMA)		
Base / Power Supply	Hard Wired		
Finish	White		
QUALIFICATIONS			
Model Number	55518		

Manufactured by P.Q.L., Inc. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice.

CF5518 XTREME DUTY • BYR LED 2' LINEAR HIGH BAY



DIMENSIONS (Inches)		
Length	23.8"	
Width	17.3″	17.3"
Height	3.6″	_
Net Weight (Lbs)		
Chain Length	41.3" (2 ea.)	

PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	1	811768027563	24.8" x 17.7" x 3.9"	20.7
Country of Origin	China			
HS Tariff	9405.10.6020			

ORDERING

ITEM#	DESCRIPTION	CASE
CF5518	LED 2FT LINEAR HIGH BAY/223W/50K/DIMM/480V	1

Manufactured by P.Q.L., Inc. - Manufacturer Model # 55518