



CF7305A XTREME DUTY • 7YR **LED STEALTH™ FIXTURE**

OUTDOOR POLE/ARM-MOUNTED AREA AND ROADWAY LUMINAIRES - ARCHITECTURAL FLOOD AND SPOT LUMINAIRES

FEATURES

- Engineered for high lumen per watt light output.
- Slim and modern appearance.
- Integrated heat sink, provides excellent thermal dissipation.
- · Surge protection device.
- Easy 1 person installation with our quick mount bracket and hinged door frame; installer can be hands free when establishing electrical connections.

APPLICATION

Parking lot, street and building perimeter lighting. Can be used as flood or area light.

ELECTRICAL

LLLUTIIIOAL		
Wattage	300W	
Voltage	200-480V	
Power Factor	0.9	
Total Harmonic Distortion (THD)	5.6	
LIGHTING PERFORMANCE		
Lumens	44185	
Lumens Per Watt (LPW)	147	
Color Temperature (CCT)	5000K	
Color Rendering (CRI)	84	
R9 (Red Value)	14	
Light Distribution	Type III	
BUG Rating (Backlight, Uplight, and Glare)	B5-U3-G4	
Dimmable Lighting Control	("Dimmable 0-10V, Range 10% - 100%	
ENVIRONMENT		
Operating Temperature	-40° ~ 131°F	
Suitable Location	WET	
Ingress Protection Rating	IP66	
LIFESPAN		
Average Life (Hours)	50,000	
Warranty (Years)	7	
COMPONENTS		
LED Light Source		
Driver	SS-320M-56BH	
CONSTRUCTION		
Housing	Aluminum	
Lens	PC	
Base / Power Supply	Hard Wire / Surge Protector	
Finish	Bronze	
Effective Projected Area (EPA)	0.42 ft²	
Wind Shear Rating	116.8 mph	
QUALIFICATIONS		
Model Number	STL3P-300W-5000K-B-MB-HC-P	




Manufactured by P.Q.L., Inc. · Published lumens on LED products are approximate and may vary slightly. · Specifications are subject to change without notice.

CF7305A XTREME DUTY • 7YR **LED STEALTH™ FIXTURE**



DIMENSIONS (Inches)

Zimizitoro (moneo)		
Length	23.4"	
Width	12"	
Height	3.6"	
Net Weight (Lbs)		



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	1	811768020649		
Country of Origin	China			
HS Tariff	9405.10.6020			

ORDERING

ITEM#	DESCRIPTION	CASE
LCF7305A	LED HL STEALTH™ 300W/50K/DIMM/480V/BRZ	1
Manufactured by	P.Q.L., Inc Manufacturer Model # STL3P-300W-5000K-B-MB-HC-P	
ACCESSORIES	S	
LFV2UB	U-BRACKET TRUNNION QUICK ATTACH/BRZ	10
LFV2RP	RIGID POLE QUICK ATTACH/BRZ	10
LFV2TN	TENON SLIPFITTER QUICK ATTACH/BRZ	10
LFSTFL	ADAPTER TO MOUNT A SLIP FITTER ON A FLAT POLE OR WALL/BRZ	20

ADDITIONAL INFORMATION:

- The mounting bracket is not included with the fixture, it is ordered as a separate item number. For DLC° qualification one of the Quick-Mount brackets must be purchased.
- Product requires top-mounted shorting cap or optional twist-lock photocell installed to operate.