



CF8126 XTREME DUTY • 7YR LED 2' LINEAR HIGH BAY

HIGH-BAY LUMINAIRES FOR COMMERCIAL AND INDUSTRIAL BUILDINGS

FEATURES

- High lumen output bright and high lumen per watt.
- Integrated LED maintenance free.
- · Replaces HID and fluorescent fixtures.
- · Wide beam angle uniform light distribution.
- All steel surfaces are painted after fabrication for smooth edges and rounded corners.

MOUNTING

Designed for suspended or pendent mounting.

APPLICATION

Larger warehouses, retail applications, commercial buildings and work areas.

ELECTRICAL

LLLUIIIIUAL		
Wattage	150W	
Voltage	120-277V	
Current	1.25A	
Power Factor	0.9	
Total Harmonic Distortion (THD)	10	
LIGHTING PERFORMANCE		
Lumens	24150	
Lumens Per Watt (LPW)	161	
Color Temperature (CCT)	5000K	
Color Rendering (CRI)	82	
R9 (Red Value)	-2	
R13 (Skin Tones)	83	
Beam Angle	120°	
Light Distribution		
BUG Rating (Backlight, Uplight, and Glare)		
Dimmable Lighting Control	Dimmable 0-10V, Range 10% - 100%	
ENVIRONMENT		
Operating Temperature	-4° ~ 122°F	
Suitable Location	DAMP	
Ingress Protection Rating	IP40	
LIFESPAN		
Average Life (Hours)	50,000	
Warranty (Years)	7	
COMPONENTS		
LED Light Source	LG LEMWS28R	
Driver	SIL100-12400 & SIL50-11200	
CONSTRUCTION		
Housing	24 Gauge C.R.S.	
Lens	Acrylic (PMMA)	
Base / Power Supply	Hard Wired	
Finish	White	
QUALIFICATIONS		
Model Number	55537	
(h)		




Manufactured by P.Q.L., Inc. · Published lumens on LED products are approximate and may vary slightly. · Specifications are subject to change without notice.

CF8126 XTREME DUTY • 7YR LED 2' LINEAR HIGH BAY



DIMENSIONS (Inches)	
Length	24.8"
Width	15"
Height	2.2"
Net Weight (Lbs)	10.4
Chain Length	41.3" (2 ea.)



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	1	811768025279		
Country of Origin	China			
HS Tariff	9405.10.6020			

ORDERING

ITEM#	DESCRIPTION	CASE
CF8126	LED 2FT LINEAR HL HIGH BAY/150W/50K/DIMM/120-277V	1
Manufactured	by P.Q.L., Inc Manufacturer Model # 55537	
ACCESSOR	IES	
LF3599	360° LOW/HIGH BAY FIXTURE OCCUPANCY PIR SENSOR 30' DIA, 8-40' HEIGHT 800W/1200W • 120/277V	50

ADDITIONAL INFORMATION:

Note: When using an Emergency Pack with the fixture, cable mounting is recommended to control the balance of the fixture.