



CLT105 XTREME DUTY • 8YR LED 2' TONE-SELECT™ LINEAR HIGH BAY

HIGH-BAY LUMINAIRES FOR COMMERCIAL AND INDUSTRIAL BUILDINGS

FEATURES

- Selectable color temperature
- High lumen output bright and high lumen per watt.
- · Integrated LED maintenance free.
- · Replaces HID and fluorescent fixtures.
- Wide beam angle uniform light distribution.
- All steel surfaces are painted after fabrication for smooth edges and rounded corners.

MOUNTING

Designed for suspended or pendent mounting.

APPLICATION

Larger warehouses, retail applications, commercial buildings and work areas.

	Eſ	TR	ırı	۸ı
CL	EL	, I N	16	۱L

Wattage	105W
Voltage	120-277V
Current	0.87A
Power Factor	0.9
Total Harmonic Distortion (THD)	10

LIGHTING PERFORMANCE

Lumens	14175
Lumens Per Watt (LPW)	135
Color Temperature (CCT)	4000K / 5000K
Color Rendering (CRI)	80
R9 (Red Value)	
R13 (Skin Tones)	
Beam Angle	120°
Light Distribution	
BUG Rating (Backlight, Uplight, and Glare)	
Dimmable Lighting Control	("Dimmable 0-10V, Range 10% - 100%

ENVIRONMENT

Operating Temperature	-4° ~ 122°F
Suitable Location	DAMP
Ingress Protection Rating	IP40

LIFESPAN

Average Life (Hours)	50,000
Warranty (Years)	8

COMPONENTS

LED Light Source	Bridgelux
Driver	Simon

CONSTRUCTION

Housing	24 Gauge C.R.S.
Lens	Acrylic (PMMA)
Base / Power Supply	Hard Wired
Finish	White

QUALIFICATIONS

Model Number	55505
--------------	-------




Manufactured by P.Q.L., Inc. - Published lumens on LED products are approximate and may vary slightly. - Specifications are subject to change without notice.

CLT105 XTREME DUTY • 8YR LED 2' TONE-SELECT™ LINEAR HIGH BAY



DIMENSIONS (Inches)	
Length	23.8"
Width	13"
Height	3.6"
Net Weight (Lbs)	10.1
Chain Length	41.34" (2 ea.)



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	1	811768026788		
Country of Origin	China			
HS Tariff	9405.10.6020			

ORDERING

ITEM#	DESCRIPTION	CASE
CLT105	LED 2FT TONE-SELECT™ LINEAR HIGH BAY/105W/40-50K/DIMM/120-277V	1
Manufactured	by P.Q.L., Inc Manufacturer Model # 55505	
ACCESSOR	IES	
LF3599	360° LOW/HIGH BAY FIXTURE OCCUPANCY PIR SENSOR 30' DIA, 8-40' HEIGHT 800W/1200W • 120/277V	50

ADDITIONAL INFORMATION:

Note: When using an Emergency Pack with the fixture, cable mounting is recommended to control the balance of the fixture.