



# LF5518 COMMERCIAL DUTY • 5YR LED 2' LINEAR HIGH BAY

HIGH-BAY LUMINAIRES FOR COMMERCIAL AND INDUSTRIAL BUILDINGS

## FEATURES

- High lumen output bright and high lumen per watt.
- Integrated LED maintenance free.
- Replaces HID and fluorescent fixtures.
- Wide beam angle uniform light distribution.
- All steel surfaces are painted after fabrication for smooth edges and rounded corners.

### MOUNTING

Designed for suspended or pendent mounting.

#### APPLICATION

Larger warehouses, retail applications, commercial buildings and work areas.

ELECTRICAL			
Wattage	223W		
Voltage	347-480V		
Current	0.63A		
Power Factor	0.9		
Total Harmonic Distortion (THD)	10		
LIGHTING PERFORMANCE			
Lumens	29213		
Lumens Per Watt (LPW)	131		
Color Temperature (CCT)	5000K		
Color Rendering (CRI)	82		
R9 (Red Value)	7.2		
R13 (Skin Tones)	83		
Beam Angle	120°		
Light Distribution	Type VS		
BUG Rating (Backlight, Uplight, and Glare)	B4 - U0 - G2		
Dimmable Lighting Control	<b>(Dimmable</b> 0-10V, Range 10% - 100%		
ENVIRONMENT			
Operating Temperature	-4° ~ 122°F		
Suitable Location	DAMP		
Ingress Protection Rating	IP40		
LIFESPAN			
Average Life (Hours)	50,000		
Warranty (Years)	5		
COMPONENTS			
LED Light Source	Seoul		
Driver	VEL100240HVHDA (2 ea.)		
CONSTRUCTION			
Housing	24 Gauge C.R.S.		
Lens	Acrylic (PMMA)		
Base / Power Supply	Hard Wired		
Finish	White		
QUALIFICATIONS			
Model Number	55518		

(U) CERTIFIED

Manufactured by P.Q.L., Inc. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice.

# LF5518 COMMERCIAL DUTY • 5YR LED 2' LINEAR HIGH BAY



DIMENSIONS (Inches)		
Length	23.8"	
Width	17.3″	· 17.3"
Height	3.6"	
Net Weight (Lbs)		
Chain Length	41.3" (2 ea.)	▶↓

23.8″ -

24.8" x 17.7" x 3.9"	20.7
	24.8" x 17.7" x 3.9"

#### ORDERING

ITEM#	DESCRIPTION	CASE
LF5518	LED 2FT LINEAR HIGH BAY/223W/50K/DIMM/480V	1

Manufactured by P.Q.L., Inc. - Manufacturer Model # 55518