



LLT210 COMMERCIAL DUTY • 5YR

- High lumen output - bright and high lumen per watt.

LED 2' TONE-SELECT™

HIGH-BAY LUMINAIRES FOR COMMERCIAL

LINEAR HIGH BAY

AND INDUSTRIAL BUILDINGS

- Selectable color temperature

Integrated LED - maintenance free.
Replaces HID and fluorescent fixtures.
Wide beam angle - uniform light distribution.
All steel surfaces are painted after fabrication for

smooth edges and rounded corners.

Designed for suspended or pendent mounting.

Larger warehouses, retail applications, commercial

FEATURES

MOUNTING

APPLICATION

buildings and work areas.

ELECTRICAL

TEMPERATURE

| Wattage | 210W | | |
|--|---|--|--|
| Voltage | 120-277V | | |
| Current | 1.75A | | |
| Power Factor | 0.9 | | |
| Total Harmonic Distortion (THD) | 10 | | |
| LIGHTING PERFORMANCE | | | |
| Lumens | 28350 | | |
| Lumens Per Watt (LPW) | 135 | | |
| Color Temperature (CCT) | 4000K / 5000K | | |
| Color Rendering (CRI) | 80 | | |
| R9 (Red Value) | | | |
| R13 (Skin Tones) | | | |
| Beam Angle | 120° | | |
| Light Distribution | | | |
| BUG Rating (Backlight, Uplight, and Glare) | | | |
| Dimmable Lighting Control | (Dimmable 0-10V, Range 10% - 100% | | |
| ENVIRONMENT | | | |
| Operating Temperature | -4° ~ 122°F | | |
| Suitable Location | DAMP | | |
| Ingress Protection Rating | IP40 | | |
| LIFESPAN | | | |
| Average Life (Hours) | 50,000 | | |
| Warranty (Years) | 5 | | |
| COMPONENTS | | | |
| LED Light Source | Bridgelux | | |
| Driver | Simon | | |
| CONSTRUCTION | | | |
| Housing | 24 Gauge C.R.S. | | |
| Lens | Acrylic (PMMA) | | |
| Base / Power Supply | Hard Wired | | |
| Finish | White | | |
| QUALIFICATIONS | | | |
| Model Number | 55508 | | |
| | | | |



Manufactured by P.Q.L., Inc. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice.

MEBULBS • WWW.MEBULBS.COM © MEBULBS • 4820 23rd Ave S STE 200 • Fargo, ND 58104 • 1-800-MEBULBS

LLT210 COMMERCIAL DUTY • 5YR LED 2' TONE-SELECT™ LINEAR HIGH BAY



| DIMENSIONS (Inches) | | |
|---------------------|----------------|--|
| Length | 23.8″ | |
| Width | 17.3″ | · · · · · · · · · · · · · · · · · · · |
| Height | 3.6" | ······································ |
| Net Weight (Lbs) | 12.6 | |
| Chain Length | 41.34" (2 ea.) | |
| | | |

— 23.8″

| PACKAGING | | UPC | DIMENSIONS (LxWxH) | GROSS WEIGHT (Lbs) |
|-------------------|--------------|--------------|--------------------|--------------------|
| Master Carton | 1 | 811768020861 | | |
| Country of Origin | China | | | |
| HS Tariff | 9405.10.6020 | | | |

ORDERING

| DESCRIPTION | CASE |
|--|--|
| LED 2FT TONE-SELECT™ LINEAR HIGH BAY/210W/40-50K/DIMM/120-277V | 1 |
| Q.L., Inc Manufacturer Model # 55508 | |
| | |
| 360° LOW/HIGH BAY FIXTURE OCCUPANCY PIR SENSOR 30' DIA, 8-40' HEIGHT 800W/1200W • 120/277V | 50 |
| | LED 2FT TONE-SELECT™ LINEAR HIGH BAY/210W/40-50K/DIMM/120-277V 0.L., Inc Manufacturer Model # 55508 |

ADDITIONAL INFORMATION:

Note: When using an Emergency Pack with the fixture, cable mounting is recommended to control the balance of the fixture.