



LC3150 COMMERCIAL DUTY • 5YR LED COMPASS HIGH BAY

HIGH-BAY LUMINAIRES FOR COMMERCIAL AND INDUSTRIAL BUILDINGS

FEATURES

- Die cast aluminum for better heat dissipation
- Dust proof and anti-corrosive
- Modern design
- High efficiency driver with built-in surge protection

APPLICATION

Ideal for commercial and industrial applications; malls, warehouses, factories, retail stores, athletic facilities, workshops, airports, and large areas.

ELECTRICAL

Wattage	150W	
Voltage	100-277V	
Power Factor	0.9	
Total Harmonic Distortion (THD)	7	
LIGHTING PERFORMANCE		
Lumens	22319	
Lumens Per Watt (Lm/W)	149	
Color Temperature (CCT)	5000K	
Color Rendering (CRI)	85	
R9 (Red Value)	17	
Beam Angle	110°	
Light Distribution	Type VS	
BUG Rating (Backlight, Uplight, and Glare)	B4 - U2 - G1	
Dimmable Lighting Control	(Dimmable 0-10V, Range 10% - 100%	
ENVIRONMENT		
Operating Temperature	-22°~ 122°F	
Suitable Location	WET	
Ingress Protection Rating	IP65	
LIFESPAN		
Average Life (Hours)	50,000	
Warranty (Years)	5	
COMPONENTS		
LED Light Source	Seoul	
Driver	LF-FHB150YAIV	
CONSTRUCTION		
Housing	Aluminum	
Lens	PC	
Base / Power Supply	Hard Wired	
Finish	Black	
QUALIFICATIONS		
Model Number	CHB3-150-D-MV-50K	





Manufactured by P.Q.L., Inc. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice.

LC3150 COMMERCIAL DUTY • 5YR LED COMPASS HIGH BAY



10.2"
6.7 ″






PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	1	811768022483		
Country of Origin	China			
HS Tariff	9405.10.6020			

ORDERING

ITEM#	DESCRIPTION	CASE
LC3150	LED COMPASS HIGH BAY/150W/50K/DIMM/100-277V/BLK	1
Manufactured	by P.Q.L., Inc Manufacturer Model # CHB3-150-D-MV-50K	
ACCESSOR	ES	
LHMTB	ADJUSTABLE ANGLE MOUNTING BRACKET FOR COMPASS HIGH BAY	20
LHSEN	MICROWAVE MOTION SENSOR FOR COMPASS HIGH BAY/100-277V 1-10V DIMM/KIT	10
LHAL16	16" ALUMINUM REFLECTOR FOR COMPASS HIGH BAY	1
LHPA16	16" ACRYLIC REFLECTOR FOR COMPASS HIGH BAY	1
LHBL16	16" ACRYLIC BOTTOM LENS FOR ACRYLIC REFLECTOR FOR COMPASS HIGH BAY	1

ADDITIONAL INFORMATION:

- Safety rope length approximately 5' 9"
- Power and dimming cord length approximately 72"
- Multiple screw holes are conveniently placed throughout the top of the fixture to connect occupancy sensors and reflectors.



Eyelet Dimensions