



LF3554 LT. COMMERCIAL • 5YR LED 2X4 PANEL

2X4 LUMINARIES FOR AMBIENT LIGHTING OF INTERIOR COMMERCIAL SPACES

FEATURES

- High Efficiency, Energy Saving
- Up to 36% Savings vs. T8 Fluorescent
- Low glare, bright consistent lighting
- · For covered ceilings only
- · Earthquake proof hooks included

APPLICATION

Ideal for offices, conference rooms, hospitals, lobbies, hotels, classrooms, workshops, cafeterias and other common areas.

ELECTRICAL

Wattage	50W	
Voltage	100-277V	
Current	1100mA	
Power Factor	0.9	
Total Harmonic Distortion (THD)	20	
LIGHTING PERFORMANCE		
Lumens	5600	
Lumens Per Watt (Lm/W)	112	
Color Temperature (CCT)	4000K	
Color Rendering (CRI)	83	
R9 (Red Value)	9	
R13 (Skin Tones)	N/A	
Beam Angle	120°	
Light Distribution	Type VS	
BUG Rating (Backlight, Uplight, and Glare)	B2 - U1 - G1	
Dimmable Lighting Control	(Dimmable 1-10V, Range 10% - 100%	
ENVIRONMENT		
Operating Temperature	-4 ~ 113°F	
Suitable Location	DAMP	
Ingress Protection Rating	IP40	
LIFESPAN		
Average Life (Hours)	50,000	
Warranty (Years)	5	
COMPONENTS		
LED Light Source	Samsung	
Driver	554336	
CONSTRUCTION		
Housing	Aluminum	
Lens		
Base / Power Supply	Hard Wired	
Finish	White	
QUALIFICATIONS		
Manufacturer Model #	55432	
CERTIFIED COMPLiant		

Manufactured by P.Q.L., Inc. • Published lumens on LED products are approximate and may vary slightly.


LF3554 LT. COMMERCIAL • 5YR LED 2X4 PANEL



DIMENSIONS (Inches)

Length	47.8″
Width/Diameter	23.7"
Height	1.7″
Weight (Lbs)	13.7

Line drawings may not be to scale and are for general reference only.



TOP VIEW

IOF VIEW

PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	2	10899645001957	49.5" x 25.6" x 4.5"	32.9
Individual Box	1	899645001950		16.5
Country of Origin	China			
HS Tariff	9405.10.6020			

ORDERING

ITEM#	DESCRIPTION	CASE
LF3554	LED 2X4 PANEL - 50W/40K/120-277V/DIMM/V6	2
New feeting days DOL Lass Manufactures Madel # 55 420		

Manufactured by P.Q.L., Inc. - Manufacturer Model # 55432