



LL3058 LT. COMMERCIAL • 5YR **LED 8" RETROFIT CAN**

INDOOR FIXTURE

FEATURES

- Energy efficient: save up to 80% in energy costs
- · High lumen output
- Instant-0n
- · For covered ceilings only
- Suitable for TYPE IC or NON-IC

APPLICATION

Ideal for retrofitting inefficient fixtures in malls, hospitals, airports, offices, lobbies and other commercial applications.

E	LE(C	K	CI	٩L

Wattage	30W	
Voltage	100-277V	
Output Voltage	36V, 700mA	
Current	0.241A	
Power Factor	0.95	
Total Harmonic Distortion (THD)	<25	
LIGHTING PERFORMANCE		
Lumens	2350	
Lumens Per Watt (Lm/W)	78	
Color Temperature (CCT)	5000K	
Color Rendering (CRI)	83	
R9 (Red Value)	3	
R13 (Skin Tones)	85	
Beam Angle	95°	
Light Distribution	Type VS	
BUG Rating (Backlight, Uplight, and Glare)	B1 - U1 - G0	
Dimmable Lighting Control	Dimmable 0-10V, Range 10% - 100%	
ENVIRONMENT		
Operating Temperature	-40° ~ 104°F	
Suitable Location	WET Indoor / Covered Ceilings	
Ingress Protection Rating	IP43	
LIFESPAN		
Average Life (Hours)	50,000	
Warranty (Years)	5	
COMPONENTS		
LED Light Source	Hongli 2835D	
CONSTRUCTION		
Housing	Aluminum Alloy	
Base / Power Supply	Hard Wired	
Finish	White	
QUALIFICATIONS		
Manufacturer Model #	90995	
(MTER) DOLLO		



Manufactured by P.Q.L., Inc. · Published lumens on LED products are approximate and may vary slightly. · Specifications are subject to change without notice.


LL3058 LT. COMMERCIAL • 5YR LED 8" RETROFIT CAN



DIMENSIONS (Inches)

Length (MOL)	5.3"	
Width/Diameter (MOD)	9.1"	
Weight (Lbs)		

Line drawings may not be to scale and are for general reference only.



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	6	10811768028611	18.9" x 17.3" x 10"	17.6
Individual Box	1	811768028614	9.2" x 5.7" x 9.1"	2.9
Country of Origin	China			
HS Tariff	8539.50.0010			

ORDERING

ITEM#	DESCRIPTION	CASE
LL3058	LED RETROFIT 8" CAN/WHITE/30W/50K/100-277V/DIMMABLE	6

Manufactured by P.Q.L., Inc. - Manufacturer Model # 90995

ADDITIONAL INFORMATION:

Production code after September 2019 (shown on the etch as 1909) will include longer lead-wires for easier EM Battery installation.