



CF6105 XTREME DUTY • 7YR LED STEALTH™ FIXTURE

OUTDOOR POLE/ARM-MOUNTED AREA AND ROADWAY LUMINAIRES - ARCHITECTURAL FLOOD AND SPOT LUMINAIRES

FEATURES

- Engineered for high lumen per watt light output.
- Slim and modern appearance.
- Integrated heat sink, provides excellent thermal dissipation.
- Surge protection device.
- Easy 1 person installation with our quick attach bracket and hinged door frame; installer can be hands free when establishing electrical connections.

APPLICATION

Parking lot, street and building perimeter lighting. Can be used as flood or area light.

ECI	DI	CI	1

Wattage	104W
Voltage	120-277V
Current	0.868A
Power Factor	0.9
Total Harmonic Distortion (THD)	13.3
LIGHTING PERFORMANCE	
,	14007

Lumens	14627
Lumens Per Watt (Lm/W)	141
Color Temperature (CCT)	5000K
Color Rendering (CRI)	84
R9 (Red Value)	12
R13 (Skin Tones)	85
Beam Angle	Type III M
Light Distribution	Type IV, Medium
Dimmable Lighting Control	(*) immable 0-10V, Range 10% - 100%
·	

ENVIRONMENT

Operating lemperature	-40° ~ 131°F
Suitable Location	WET
Ingress Protection Rating	IP66

LIFESPAN

Average Life (Hours)	50,000
Warranty (Years)	7

COMPONENTS

LED Light Source	Luxeon 3030 2D
Driver	Sosen SS-100E-58B

CONSTRUCTION

Housing	Aluminum		
Lens	PC		
Base / Power Supply	Hard Wired / Surge Protector		
Finish	Bronze		
Effective Projected Area (EPA)	0.23ft ²		

QUALIFICATIONS

Manufacturer Model #	L-STL-100-5000K-MV-D-YY-ZZ-3
Managaria Model #	L-31L-100-3000K-WW-D-11-ZZ-3



Manufactured by P.Q.L., Inc.- Published lumens on LED products are approximate and may vary slightly.


CF6105 XTREME DUTY • 7YR **LED STEALTH™ FIXTURE**



DIMENSIONS (Inches)

Length (MOL)	16.8"
Width/Diameter (MOD)	12"
Height	3.5"
Weight (Lbs)	

Line drawings may not be to scale and are for general reference only.



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	1	811768028232	18.5" x 13.8" x 13.8"	10
Country of Origin	China			
HS Tariff	9405.40.8200			

ORDERING*

ITEM#	DESCRIPTION	CASE	
CF6105	LED STEALTH™ 100W/50K/120-277V/DIMMABLE/BRONZE/V2	1	
Manufactured b	Manufactured by P.Q.L., Inc Manufacturer Model # L-STL-100-5000K-MV-D-YY-ZZ-3		
ACCESSORI	IES/REPLACEMENT PARTS		
LFV2UB	U-BRACKET TRUNNION QUICK ATTACH	10	
LFV2RP	RIGID POLE QUICK ATTACH	10	
LFV2TN	TENON SLIPFITTER QUICK ATTACH	10	

ADDITIONAL INFORMATION:

*The mounting bracket is not included with the fixture, it is ordered as a separate item number. To qualify for rebates one of the Quick-Attach brackets must be purchased