



CMFX60 XTREME DUTY • 7YR LED SPEC-SELECT[™] FLOOD LIGHT

FEATURES

- Adjustable wattage and color temperature.
- Integrated photocell with On/Off switch.
- Corrosion resistant die cast housing, with a powder paint coat finish.
- Compact design.
- Fixture angle can be easily adjusted.

APPLICATION

Ideal for wall washing, landscaping lighting, outdoor advertising and parking lots.

Wattage	35W / 50W / 60W		
Voltage	120-277V		
Power Factor	0.9		
Total Harmonic Distortion (THD)	20		
LIGHTING PERFORMANCE			
Lumens	5075 / 7250 / 8700		
Lumens Per Watt (LPW)	145		
Color Temperature (CCT)	3000K / 4000K / 5000K		
Color Rendering (CRI)	83		
R9 (Red Value)	5		
R13 (Skin Tones)			
Beam Angle	7H x 7V		
Light Distribution	Type VS		
BUG Rating (Backlight, Uplight, and Glare)	B3 - Ux - G1		
Dimmable Lighting Control	(Dimmable 0-10V, Range 10% - 100%		
ENVIRONMENT			
Operating Temperature	-4° ~ 104°F		
Suitable Location	WET		
Ingress Protection Rating	IP65		
LIFESPAN			
Average Life (Hours)	50,000		
Warranty (Years)	7		
COMPONENTS			
LED Light Source			
Driver	Premium Electronics		
	with 6kV/4kV Surge Protection		
CONSTRUCTION			
Housing	Die Cast Aluminum		
Lens	PC		
Base / Power Supply	Hard Wired		
Finish	Bronze		
QUALIFICATIONS			
Manufacturer Model #	84361		



Manufactured by P.Q.L., Inc. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice.

CMFX60 XTREME DUTY • 7YR LED SPEC-SELECT™ FLOOD LIGHT



DIMENSIONS (Inches) Length Width Height Weight (Lbs)	79" 2.1" 9.1" 	5.9"	79"	
PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	6	10811768025955	16.3" x 8.1" x 10.6"	
Individual Box	1	811768025958	8" x 2.6" x 10.4"	
Country of Origin	China			
HS Tariff	9405.11.6020			

ORDERING

ITEM#	DESCRIPTION	CASE
CMFX60	LED SPEC-SELECT™ FL00D/35-50-60W/30-40-50K/DIMM/120-277V/BRZ/PC • 1/2IN KNUCKLE	6
Manufacturad by DOL Inc. Manufacturar Madal # 24261		

Manufactured by P.Q.L., Inc. - Manufacturer Model # 84361