

SELECTABLE COLOR TEMPERATURE TONE-SELECT™

CMRT53 COMMERCIAL DUTY • 5YR

5.5W LED TONE-SELECT™ MR16 LAMP REFLECTOR (NARROW FLOOD)

FEATURES

The LED TONE-SELECT™ MR16 lamp offers the flexibility to select the ideal color temperature for any application while delivering bright, energy efficient lighting, excellent color rendering, and long-lasting performance..

- Selectable CCT: Choose from three color temperature options.
- Ideal replacement for traditional 50W MR16 halogen lamps.

APPLICATION

Commercial and residential applications including track lighting, recessed fixtures, display lighting, accent lighting, and landscape applications.

ELECTRICAL	
Wattage	5.5W
Voltage	12V
Current	70mA

LIGHTING PERFORMANCE	
Lumens	500
Lumens Per Watt (Lm/W)	91
Color Temperature (CCT)	3000K/4000K/5000K
Color Rendering (CRI)	90
Beam Angle	40°
Dimmable Lighting Control	See Install Instructions

ENVIRONMENT	
Operating Temperature	-4° ~ 104°F
Suitable Location	Damp
IP Rating	IP20
Suitable Fixture Type	Open

LIFESPAN	
Average Life (Hours)	15,000
Warranty (Years)	**5**

CONSTRUCTION	
Housing	PC
Base	GU5.3
Finish	White

QUALIFICATIONS

UL CERTIFIED

Manufactured by P.Q.L., Inc. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice.

© **MEBULBS** • 4837 Amber Valley Pkwy S STE 500 • Fargo ND, 58104 • 1-800-MEBULBS

Specifications are subject to change without notice. Photos and line drawings may not be to scale and are for general reference only.
REV. 11-24-26

CMRT53 COMMERCIAL DUTY • 5YR
5.5W LED TONE-SELECT™ MR16 LAMP

MEBULBS SINCE 1974

ITEM INFORMATION

DIMENSIONS (Inches)	
Width/Diameter (MOD)	2.0″
Height	1.8″
Net Weight (Lbs)	--

PACKAGING	
Master Case	100
Dimensions	10.6″ x 10.6″ x 10.2″
Country of Origin	China
HS Tariff	8539.52.00.40



ORDERING

ITEM#	DESCRIPTION	CASE
CMRT53	5.5W MR16/30-40-50K/FL40	100

Manufactured by P.Q.L., Inc. - Manufacturer Model # MR1663CGU531

© **MEBULBS** • 4837 Amber Valley Pkwy S STE 500 • Fargo ND, 58104 • 1-800-MEBULBS

Specifications are subject to change without notice. Photos and line drawings may not be to scale and are for general reference only.
REV. 11-24-26