



## **CRC255** XTREME DUTY • 7YR **LED HIGH WATTAGE 360° LAMP** REPLACEMENT LAMPS FOR OUTDOOR POLE/ARM

MOUNTED DECORATIVE LUMINAIRES (TYPE B)

## FEATURES

- Uses patented remote activated phosphor technology which increases lifespan by reducing temperatures.

- More consistent light output and color stability.
- High lumen output.
- 360° optical design that provides even light distribution.
- Surge Protection (5KV).
- Replaces high pressure sodium metal halide lamps.

## **APPLICATION**

Replacement lamps for top post, high bays, parking lots and street lighting.

\*Not suitable for use with emergency fixtures.

Wattage	25W		
Voltage	120-277V		
Current	0.2A		
Power Factor	0.9		
Total Harmonic Distortion (THD)			
LIGHTING PERFORMANCE			
Lumens	3625		
Lumens Per Watt (Lm/W)	145		
Color Temperature (CCT)	5000K		
Color Rendering (CRI)	80		
R9 (Red Value)	9		
R13 (Skin Tones)	84		
Beam Angle	270°		
Light Distribution	Type VS		
BUG Rating (Backlight, Uplight, and Glare)	B1 - U4 - G2		
Dimmable Lighting Control	CITE MARKET		
ENVIRONMENT			
Operating Temperature	-13° ~ 131°F		
Suitable Location	DAMP		
Ingress Protection Rating	IP64		
Fixture Type	Enclosed		
LIFESPAN			
Average Life (Hours)	50,000		
Warranty (Years)	7		
COMPONENTS			
LED Light Source	2835 LED		
CONSTRUCTION			
Housing	Aluminum / PC		
Lens	Yellow - Off / White - O		
Base / Power Supply	E26 - Medium		
QUALIFICATIONS			
Manufacturer Model #	91805		



Manufactured by P.Q.L., Inc. • Published lumens on LED products are approximate and may vary slightly.


# CRC255 XTREME DUTY • 7YR LED HIGH WATTAGE 360° LAMP



#### **DIMENSIONS** (Inches)

Length (MOL)	7.4″
Width/Diameter (MOD)	3.3"
Weight (Lbs)	

Line drawings may not be to scale and are for general reference only.



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	20	10811768020165	20.9" x 16.9" x 9.5"	17.5
Individual Box	1	811768020168	3.6" x 3.6" x 8"	0.9
Country of Origin	China			
HS Tariff	8539.50.0010			

### ORDERING

ITEM#	DESCRIPTION	CASE
CRC255	LED 25WT26/360°/50K/MED/120-277V	20

Manufactured by P.Q.L., Inc. - Manufacturer Model # 91805