



LF3014 LT. COMMERCIAL • 5YR LED 1x4 LOUVERED HIGH BAY

HIGH-BAY LUMINAIRES FOR COMMERCIAL And Industrial Buildings

FEATURES

- Provides smooth uniform light.
- Low-profile which meets limitless range of applications.
- Use 30% less energy than a linear fluorescent fixtures
- Die formed 24 gauge cold rolled steel.
- All steel surfaces are painted after fabrication with high gloss baked white matte powder paint.

APPLICATION

Ideal for larger warehouses, retail applications, commercial buildings and work areas.

ELECTRICAL

CERTIFIED

Wattage	90W		
Voltage	120-277V		
Power Factor	0.9		
Total Harmonic Distortion (THD)	10		
LIGHTING PERFORMANCE			
Lumens	11700		
Lumens Per Watt (Lm/W)	130		
Color Temperature (CCT)	4000K		
Color Rendering (CRI)	80		
R9 (Red Value)			
R13 (Skin Tones)			
Beam Angle	120°		
Light Distribution	Type VS		
Dimmable Lighting Control	(Dimmable 0-10V, Range 10% - 100%		
ENVIRONMENT			
Operating Temperature	-4° ~ 122°F		
Suitable Location	DAMP		
Ingress Protection Rating	IP40		
LIFESPAN			
Average Life (Hours)	50,000		
Warranty (Years)	5		
COMPONENTS			
LED Light Source	Seoul STWxA2PD-xx		
Driver	Simon SI 80-I2000 120-277 W D1 S		
CONSTRUCTION			
Housing	24 Gauge Steel		
Base / Power Supply	Hard Wired		
Finish	White		
QUALIFICATIONS			
Manufacturer Model #	55187		

Manufactured by P.Q.L., Inc. • Published lumens on LED products are approximate and may vary slightly.


LF3014 LT. COMMERCIAL • 5YR LED 1x4 LOUVERED HIGH BAY



DIMENSIONS (Inches)

Length	48.1"
Width/Diameter	9.8″
Height	4.2"
Weight (Lbs)	

Line drawings may not be to scale and are for general reference only.



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	1	811768027440		
Country of Origin	China			
HS Tariff				

ORDERING					
ITEM#	DESCRIPTION	CASE			
LF3014	LED 1x4 LOUVERED HIGH BAY - 90W/40K/120-277V/DIMMABLE	1			
Manufactured	by P.Q.L., Inc Manufacturer Model # 55187				
ACCESSOR	NES/REPLACEMENT PARTS				
LF3599	HIGH BAY/LOW BAY PASSIVE INFRARED OCCUPANCY SENSOR	50			