

FEATURES



OUTDOOR POLE/ARM-MOUNTED AREA AND ROADWAY LUMINAIRES ARCHITECTURAL FLOOD AND SPOT LUMINAIRES

- Elegant and modern appearance
- Die cast aluminum housing
- Lifespan of 50,000 hours or more
- Type III Light Distribution
- IP Grade: IP65

APPLICATION



Parking lot, street and building perimeter lighting.

SPECIFICATIONS

Power Consumption	60W
Input Voltage	100-277V
Power Factor	0.9
Lumens	7700
Luminous Efficiency	128 Lm/W
Color Temperature	5000K
CRI	80
Beam Angle	130°
Finish	Bronze
Dimensions (Inches)	23.7"(L) x 11.2"(W) x 3.4"(H)
Weight	4.5kg / 9.9 lbs
LED	
LED Driver	Sosen SS-75H-42
LED Type	Philips
LIFESPAN & ENVIRONMENT	
Average Life	50,000
Operating Temperature	-30°C ~ 45°C



DIMENSIONS



ORDERING

ITEM#	DESCRIPTION	WATTS	COLOR	LUMENS	CRI	VOLT	HOUSING	HOURS	CASE
CF/LF5065	LED STEALTH™ SHOE BOX 60W/50K/100-277V-SLIP FITTER/BRONZE 83588	60	5000K	7700	80	100-277V	BRONZE	50,000	1