

LF7305A COMMERCIAL DUTY • 5YR
LED STEALTH™ FIXTURE
OUTDOOR POLE/ARM-MOUNTED AREA AND
ROADWAY LUMINAIRES • ARCHITECTURAL FLOOD
AND SPOT LUMINAIRES

FEATURES

- Engineered for high lumen per watt light output.
- Slim and modern appearance.
- Integrated heat sink, provides excellent thermal dissipation.
- Surge protection device.
- Easy 1 person installation with our quick mount bracket and hinged door frame; installer can be hands free when establishing electrical connections.

APPLICATION

Parking lot, street and building perimeter lighting. Can be used as flood or area light.

ELECTRICAL

Wattage	300W
Voltage	200-480V
Power Factor	0.9
Total Harmonic Distortion (THD)	5.6

LIGHTING PERFORMANCE

Lumens	44185
Lumens Per Watt (LPW)	147
Color Temperature (CCT)	5000K
Color Rendering (CRI)	84
R9 (Red Value)	14
Light Distribution	Type III
BUG Rating (Backlight, Uplight, and Glare)	B5-U3-G4
Dimmable Lighting Control	<i>Dimmable</i> 0-10V, Range 10% - 100%

ENVIRONMENT

Operating Temperature	-40° ~ 131°F
Suitable Location	WET
Ingress Protection Rating	IP66

LIFESPAN

Average Life (Hours)	50,000
Warranty (Years)	5

COMPONENTS

LED Light Source	--
Driver	SS-320M-56BH

CONSTRUCTION

Housing	Aluminum
Lens	PC
Base / Power Supply	Hard Wire / Surge Protector
Finish	Bronze
Effective Projected Area (EPA)	0.42 ft ²
Wind Shear Rating	116.8 mph

QUALIFICATIONS

Model Number	STL3P-300W-5000K-B-MB-HC-P
--------------	----------------------------




Manufactured by P.Q.L., Inc. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice.

LF7305A COMMERCIAL DUTY • 5YR LED STEALTH™ FIXTURE



ITEM INFORMATION

DIMENSIONS (Inches)	
Length	23.4"
Width	12"
Height	3.6"
Net Weight (Lbs)	--



PACKAGING	UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	1	811768020649	--
Country of Origin	China		
HS Tariff	9405.10.6020		

ITEM#	DESCRIPTION	CASE
LF7305A	LED HL STEALTH™ 300W/50K/DIMM/480V/BRZ	1
<i>Manufactured by P.Q.L., Inc. - Manufacturer Model # STL3P-300W-5000K-B-MB-HC-P</i>		

ACCESSORIES		
ITEM#	DESCRIPTION	CASE
LFV2UB	U-BRACKET TRUNNION QUICK ATTACH/BRZ	10
LFV2RP	RIGID POLE QUICK ATTACH/BRZ	10
LFV2TN	TENON SLIPFITTER QUICK ATTACH/BRZ	10
LFSTFL	ADAPTER TO MOUNT A SLIP FITTER ON A FLAT POLE OR WALL/BRZ	20

- ADDITIONAL INFORMATION:**
- The mounting bracket is not included with the fixture, it is ordered as a separate item number. For DLC® qualification one of the Quick-Mount brackets must be purchased.
 - Product requires top-mounted shorting cap or optional twist-lock photocell installed to operate.