



**LF8128 COMMERCIAL DUTY • 5YR
LED 2' LINEAR HIGH BAY**
HIGH-BAY LUMINAIRES FOR COMMERCIAL AND
INDUSTRIAL BUILDINGS

FEATURES

- High lumen output - bright and high lumen per watt.
- Integrated LED - maintenance free.
- Replaces HID and fluorescent fixtures.
- Wide beam angle - uniform light distribution.
- All steel surfaces are painted after fabrication for smooth edges and rounded corners.

MOUNTING

Designed for suspended or pendent mounting.

APPLICATION

Larger warehouses, retail applications, commercial buildings and work areas.

ELECTRICAL

Wattage	175W
Voltage	120-277V
Current	1.45A
Power Factor	0.9
Total Harmonic Distortion (THD)	10

LIGHTING PERFORMANCE

Lumens	28175
Lumens Per Watt (LPW)	161
Color Temperature (CCT)	5000K
Color Rendering (CRI)	82
R9 (Red Value)	-7
R13 (Skin Tones)	--
Beam Angle	120°
Light Distribution	--
BUG Rating (Backlight, Uplight, and Glare)	--
Dimmable Lighting Control	<i>Dimmable</i> 0-10V, Range 10% - 100%

ENVIRONMENT

Operating Temperature	-4° ~ 122°F
Suitable Location	DAMP
Ingress Protection Rating	IP40

LIFESPAN

Average Life (Hours)	50,000
Warranty (Years)	5

COMPONENTS

LED Light Source	LG 2835
Driver	Simon

CONSTRUCTION

Housing	24 Gauge C.R.S.
Lens	Acrylic (PMMA)
Base / Power Supply	Hard Wired
Finish	White

QUALIFICATIONS

Model Number	55539
--------------	-------




Manufactured by P.Q.L., Inc. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice.

LF8128 COMMERCIAL DUTY • 5YR LED 2' LINEAR HIGH BAY



ITEM INFORMATION

DIMENSIONS (Inches)	
Length	24.8"
Width	18.9"
Height	2.2"
Net Weight (Lbs)	11.2
Chain Length	41.3" (2 ea.)



PACKAGING	UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	1	811768023152	--
Country of Origin	China		
HS Tariff	9405.10.6020		

ORDERING		
ITEM#	DESCRIPTION	CASE
LF8128	LED 2FT LINEAR HL HIGH BAY/175W/50K/DIMM/120-277V	1

Manufactured by P.Q.L., Inc. - Manufacturer Model # 55539

ACCESSORIES		
LF3599	360° LOW/HIGH BAY FIXTURE OCCUPANCY PIR SENSOR 30' DIA, 8-40' HEIGHT 800W/1200W • 120/277V	50

ADDITIONAL INFORMATION:

Note: When using an Emergency Pack with the fixture, cable mounting is recommended to control the balance of the fixture.