



LLB344 STANDARD • 5YR LED BALLAST BYPASS LINEAR T8

INTERNAL DRIVER LAMP-STYLE RETROFIT KITS (UL TYPE B)

FEATURES

Our T8 LED tube lamp provides exceptional LED lighting with reduced energy and maintenance costs. The linear LED does not use a fluorescent ballast to work; instead they feature a built-in universal line voltage driver, making it a top of the line replacement for standard fluorescent lamps.

SINGLE ENDED DIRECT WIRE

- No ballast required, lamp runs off main
- Exceptional efficacy

**Non-shunted sockets required, see install instructions for further details.

ELECTRICAL

ELECTRICAL		
Wattage	14W	
Voltage	120-277V	
Current	117-55mA	
Power Factor	0.9	
Total Harmonic Distortion (THD)	<20	
LIGHTING PERFORMANCE		
Lumens	1800	
Lumens Per Watt (Lm/W)	128	
Color Temperature (CCT)	4000K	
Color Rendering (CRI)	80	
R9 (Red Value)	10	
R13 (Skin Tones)	85	
Beam Angle	140°	
Light Distribution	Type VS	
Dimmable Lighting Control	NOT COMPANY	
ENVIRONMENT		
Operating Temperature	-13° ~ 104°F	
Suitable Location	DAMP	
Ingress Protection Rating	IP20	
Suitable Fixture Type	Enclosed	
LIFESPAN		
Average Life (Hours)	50,000	
Warranty (Years)	5	
COMPONENTS		
LED Light Source	Smalite	
CONSTRUCTION		
Housing	Glass / Plastic End Caps	
Lens	Frosted	
Base / Power Supply	G13 - Medium Bi Pin	
QUALIFICATIONS		
Manufacturer Model #	91086	
Rohs compliant		


Manufactured by P.Q.L., Inc. • Published lumens on LED products are approximate and may vary slightly.

LLB344 STANDARD • 5YR LED BALLAST BYPASS LINEAR T8



DIMENSIONS (Inches)

Length	48"
Width/Diameter	1″
Weight (Lbs)	



Line drawings may not be to scale and are for general reference only.

PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	25	10811768027010		
Individual Box	1	811768027013		
Country of Origin	China			
HS Tariff	9405.40.8200			

ORDERING

ITEM#	DESCRIPTION	CASE
LLB344	LED 4' 14WT8/40K/FR CEE	25
Manufactured by P.Q.L., Inc Manufacturer Model # 91086		

PERFORMANCE DATA