

FEATURES



Our T8 LED tube can work with the most popular electronic ballasts that are capable of replacing your existing fluorescent T8 lamps without any additional wiring. It provides exceptional LED lighting with reduced energy and maintenance costs.

- **PLUG & GO™ - WORKS WITH EXISTING ELECTRONIC BALLAST***
- **Construction:** Frosted Glass / Plastic End Caps
- Exceptional efficacy
- No flickering
- IP20

***Suitable for dimming and emergency ballasts.*


SPECIFICATIONS

| Lamp Power | 9W |
|------------------------|--------------------|
| Input Voltage | 120-277V |
| Power Factor | 0.9 |
| THD | 13.3 |
| Lumens | 1350 |
| Luminous Efficiency | 112 Lm/W |
| Color Temperature | 4000K |
| CRI | 83 |
| Beam Angle | 160° |
| Dimension (Inches) | 23.6"(L) x 1"(DIA) |
| LIFESPAN & ENVIRONMENT | |
| Average Life | 50,000 |
| Operating Temperature | -20°C ~ 45°C |

SUITABLE FOR
DAMP
LOCATIONS



DIMENSIONS



ORDERING

| ITEM# | DESCRIPTION | WATT | LED | COLOR | LUMENS | CRI | VOLT | HOURS | CASE |
|------------|---------------------------------------|------|-----|-------|--------|-----|----------|--------|------|
| CLR/LLR024 | LED 2' 9WT8/40K/FR/PLUG & GO/V5 91324 | 9 | SMD | 4000K | 1350 | 83 | 120-277V | 50,000 | 25 |