



LLR144 STANDARD • 5YR **LED DIRECT INSTALL LINEAR T8 REPLACEMENT LAMPS (PLUG AND PLAY)** (UL TYPE A)

FEATURES

Our T8 LED tube can work with the most popular electronic ballasts that are capable of replacing your existing fluorescent T8 lamps without any additional wiring. It provides exceptional LED lighting with reduced energy and maintenance costs.

WORKS WITH EXISTING ELECTRONIC BALLAST*

- Exceptional efficacy
- · No flickering
- *Suitable for dimming and emergency ballasts.

ELECTRICAL	LAMP	SYSTEM POWER	
Wattage	14W	16W	
Voltage	120	120-277V	
Power Factor	(0.9	
Total Harmonic Distortion (THD)	20		
LIGHTING PERFORMANCE			
Lumens	22	200	
Lumens Per Watt (LPW)	138		
Color Temperature (CCT)	4000K		
Color Rendering (CRI)	82		
R9 (Red Value)	12		
R13 (Skin Tones)	84		
Beam Angle	190°		
Light Distribution			
BUG Rating (Backlight, Uplight, and Glare)			
Dimmable Lighting Control	Compatible with select dimming ballasts.		
ENVIRONMENT			
Operating Temperature	-4° ~ 113°F		
Suitable Location	DAMP		
Ingress Protection Rating	IP20		
Suitable Fixture Type	Enclosed		
LIFESPAN			
Average Life (Hours)	50,000		
Warranty (Years)	5		
COMPONENTS			
LED Light Source	Lumileds		
CONSTRUCTION			
Housing	Glass / Plastic End Caps		
Lens	Frosted		
Base / Power Supply	G13 - Medium Bi Pin		
QUALIFICATIONS			
Manufacturer Model #	91835		
ROHS COMPLIANT CEETING			




Manufactured by P.Q.L., Inc. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice.

LLR144 STANDARD • 5YR LED DIRECT INSTALL LINEAR T8



DIMENSIONS (Inches)

Length (MOL)	47.8"	
Width/Diameter (MOD)	1"	
Net Weight (Lbs)		



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	25	10811768028031	48.8" x 5.9" x 5.9"	14.8
Individual Box	1	811768028034		0.59
Country of Origin	China			
HS Tariff	8539.50.0050			

ORDERING

ITEM#	DESCRIPTION	CASE
LLR144	LED 4FT 14WT8/40K/TYPE A - CEE	25

Manufactured by P.Q.L., Inc. - Manufacturer Model # 91835