



LM3755 LT. COMMERCIAL • 5YR LED HIGH WATTAGE 360° LAMP

REPLACEMENT LAMPS FOR OUTDOOR POLE/ARM MOUNTED DECORATIVE LUMINAIRES (TYPE B)


FEATURES

- Environmentally friendly; uses less energy than a traditional lamp.
- 360° optical design that provides even light distribution.
- · High Voltage Surge Protection (6KV).
- Hollow heat sink for increased cooling air flow.
- High lumen output.
- · Silicone gaskets.


APPLICATION

Replacement lamps for top post, high bays, parking lots and street lighting.

LIGHT DISTRIBUTION CURVE



ELECTRICAL	ITEM	DLC WHOLE FIXTURE
Wattage	75W	73W
Voltage	120-277V	
Current	0.75A	
Power Factor		0.9
Total Harmonic Distortion (THD)		13.1
LIGHTING PERFORMANCE		
Lumens	9750	8532
Lumens Per Watt (Lm/W)	130	117
Color Temperature (CCT)	5000K	
Color Rendering (CRI)	82	
R9 (Red Value)	N/A	
R13 (Skin Tones)	N/A	
Beam Angle	360°	
Light Distribution	Type VS	
Dimmable Lighting Control	Aust Transact A	
ENVIRONMENT		
Operating Temperature	-40° ~ 122°F	
Suitable Location	DAMP	
Ingress Protection Rating	IP63	
Suitable Fixture Type	Enclosed	
LIFESPAN		
Average Life (Hours)	50,000	
Warranty (Years)	5	
COMPONENTS		
LED Light Source	JuFei 2835	
CONSTRUCTION		
Housing	Aluminum / PC	
Lens	Clear	
Base / Power Supply	E39 - Mogul	
QUALIFICATIONS		
Manufacturer Model #	9	1582
CERTIFIED ROHS COMPliant		




LM3755 LT. COMMERCIAL • 5YR LED HIGH WATTAGE 360° LAMP



DIMENSIONS (Inches)

Length (MOL)	12"
Width/Diameter (MOD)	3.7"
Weight (Lbs)	

Line drawings may not be to scale and are for general reference only.



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	12	10811768028529	18" x 13.5" x 14.8"	
Individual Box	1	811768028522	4.3" x 4.3" x 14"	
Country of Origin	China			
HS Tariff	9405.40.8200			

ORDERING

ITEM#	DESCRIPTION	CASE
LM3755	LED 75WT30/360°/CL/50K/M0G/120-277V DLC	12

Manufactured by P.Q.L., Inc. - Manufacturer Model # 91582 · Visit www.designlights.org/search to confirm qualification.

ADDITIONAL INFORMATION:

TOP VIEW

