



LMD345 COMMERCIAL DUTY • 5YR LED SNAP & GO™ MAGNETIC MODULES

LINEAR RETROFIT KITS FOR 2X4 LUMINAIRES

FEATURES

- Replacements for traditional fluorescent fixtures and recessed troffers in drop-in ceilings
- Quick connect
- · Magnetic mounting
- · Innovative design

APPLICATION

Ideal for retrofitting existing fluorescent fixtures and recessed troffers.

:rt	DІ	CAL
	nı	UAL

ELECIKICAL		
Wattage	40W	
Voltage	100-277V	
Current	445mA	
Power Factor	0.9	
Total Harmonic Distortion (THD)	9.3	
LIGHTING PERFORMANCE		
Lumens	4650	
Lumens Per Watt (Lm/W)	116	
Color Temperature (CCT)	5000K	
Color Rendering (CRI)	85	
R9 (Red Value)	16	
R13 (Skin Tones)	86	
Beam Angle	140°	
Light Distribution	Type VS	
BUG Rating (Backlight, Uplight, and Glare)	B2 - U1 - G1	
Dimmable Lighting Control	(Dimmable 0-10V, Range 10% - 100%	
ENVIRONMENT		
Operating Temperature	-13° ~ 113°F	
Suitable Location	DAMP	
Ingress Protection Rating	IP20	
Fixture Type	Enclosed	
LIFESPAN		
Average Life (Hours)	50,000	
Warranty (Years)	5	
COMPONENTS		
LED Light Source	Jufei 2835	
Driver	938096	
CONSTRUCTION		
Housing	Plastic	
Lens	Frosted	
Base / Power Supply	Hard Wired	
QUALIFICATIONS		
Model Number	93809	
(T) Rous		




Manufactured by P.Q.L., Inc. · Published lumens on LED products are approximate and may vary slightly. · Specifications are subject to change without notice.

LMD345 COMMERCIAL DUTY • 5YR LED SNAP & GO™ MAGNETIC MODULES



DIMENSIONS (Inches)	MODULES	DRIVER
Length	43.4"	9.1"
Width	0.7"	1.2"
Height	0.7"	0.7"
Net Weight (Lbs)		



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	10	10811768029533	46" x 11" x 7.1"	21.2
Individual Box	1	811768029536		2.1
Country of Origin	China			
HS Tariff	9405.10.6020			

ORDERING

ITEM#	DESCRIPTION	CASE
LMD345	LED SNAP & GO™ MAGNETIC MODULES/40W/50K/FR/DIMM/100-277V • 3X4FT	10

Manufactured by P.Q.L., Inc. - Manufacturer Model # 93809