



## LSH245 COMMERCIAL DUTY • 5YR LED HYBRID LINEAR T5

DUAL MODE INTERNAL DRIVER (UL TYPE A AND TYPE B)

### **FEATURES**

The LED T5 Linear Hybrid tubes provides exceptional lighting with reduced energy and maintenance costs. The hybrid tube works with or without a ballast, making it a top-of-the-line replacement for standard fluorescent lamps.

### DIRECT INSTALL OR DIRECT WIRE SINGLE / DOUBLE ENDED

Use with an instant start ballast as a direct replacement lamp or simple rewiring allows lamp to run directly off the main.

- · Wide beam design
- Exceptional efficacy

ELECTRICAL	LAMP	SYSTEM Power
Wattage	24W	27.5W
Voltage	120-277V	
Current	22	2mA
Power Factor	0.9	
Total Harmonic Distortion (THD)	20	
LIGHTING PERFORMANCE		
Lumens	3300	
Lumens Per Watt (LPW)	120	
Color Temperature (CCT)	5000K	
Color Rendering (CRI)	80	
R9 (Red Value)	10	
Beam Angle	180°	
Light Distribution	Type VS	
Dimmable Lighting Control	See Install Instructions	
ENVIRONMENT		
Operating Temperature	-4° ~ 113°F	
Suitable Location	DAMP	
Ingress Protection Rating	IP20	
Suitable for Emergency Fixtures/Ballasts	No	
LIFESPAN		
Average Life (Hours)	50,000	
Warranty (Years)	5	
CONSTRUCTION		
Housing	Glass / Plastic End Caps	
Lens	Frosted / Safety Coated	
Base / Power Supply	G5 - Mini Bi Pin	
QUALIFICATIONS		
Model Number	91838	




Manufactured by P.Q.L., Inc. · Published lumens on LED products are approximate and may vary slightly. · Specifications are subject to change without notice.

# LSH245 COMMERCIAL DUTY • 5YR LED HYBRID LINEAR T5



DIMENSIONS (Inches)	
Length (MOL)	45.8"
Width/Diameter (MOD)	0.6"
Net Weight (Lbs)	



PACKAGING		UPC	<b>DIMENSIONS</b> (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	25	10811768029755	46.8" x 4.9" x 5.3"	
Individual Item		811768029758	N/A	N/A
Country of Origin	China			
HS Tariff				

### **ORDERING**

ITEM#	DESCRIPTION	CASE
LSH245	LED 4FT 24WT5/50K/TYPE A & B/SAFETY COATED	25

Manufactured by P.Q.L., Inc. - Manufacturer Model # 91838