





LVEX60 COMMERCIAL DUTY • 5YR LED VERSA-TOP™

OUTDOOR POLE/ARM-MOUNTED DECORATIVE LUMINAIRES

FEATURES

- VERSA-TOP™ features adjustable wattage and color temperature for the perfect balance of light in any application.
- · Integrated LED maintenance free.
- Replaces a wide range of HID fixtures.
- Elegant and modern appearance.
- Corrosion resistant; powder coated aluminum housing.
- · Surge protection.

MOUNTING BRACKETS

Multiple Options; Single Arm, Double Arm, Slip Fitter, Ceiling Mount, Conduit and Straight Arm (*Brackets sold separately.*)

APPLICATION

Walkway and building perimeter lighting. Can be used as flood or area light.

ELECTRICAL

| Wattage | 18W / 30W / 50W / 60W |
|---------------------------------|-----------------------|
| Voltage | 120-277V |
| Current | 60W = 0.5A @ 120V |
| Power Factor | 0.9 |
| Total Harmonic Distortion (THD) | 10 |

LIGHTING PERFORMANCE

| Lumens | 2988 / 4530 / 7607 / 9128 |
|--|---|
| Lumens Per Watt (LPW) | 166 / 151 / 152 / 152 |
| Color Temperature (CCT) | 3000K / 4000K / 5000K |
| Color Rendering (CRI) | 70 |
| R9 (Red Value) | -36 |
| Light Distribution | Type VS |
| BUG Rating (Backlight, Uplight, and Glare) | B2 - U1 - G1 |
| Dimmable Lighting Control | (Dimmable 0-10V, Range 10% - 100% |

ENVIRONMENT

| Operating Temperature | -22° ~ 122°F | |
|---------------------------|--------------|--|
| Suitable Location | WET | |
| Ingress Protection Rating | IP66 | |
| Impact Rating | IK08 | |
| | | |

LIFESPAN

| Average Life (Hours) | 50,000 |
|----------------------|--------|
| Warranty (Years) | 5 |

COMPONENTS

| LED Light Source | Luxeon 3030 |
|------------------|-------------|
| Driver | WP-CLB-60U |

CONSTRUCTION

| Housing | Aluminum Alloy | |
|--------------------------------|--------------------------|--|
| Lens | PC Lens + Tempered Glass | |
| Base / Power Supply | Hard Wired | |
| Finish | Black | |
| Effective Projected Area (EPA) | 1.2 ft² | |

QUALIFICATIONS

| Model Numbers | SSDPT-60W-CCT-D-M-18, SSDPT-30W-CCT-D-M, |
|---------------|--|
| | SSDPT-50W-CCT-D-M, SSDPT-60W-CCT-D-M |




Manufactured by P.Q.L., Inc. · Published lumens on LED products are approximate and may vary slightly. · Specifications are subject to change without notice.

LVEX60 COMMERCIAL DUTY • 5YR **LED VERSA-TOP™**



DIMENSIONS (Inches)

| Difficitorio (menes) | |
|----------------------|-------|
| Width (MOD) | 15.8" |
| Height | 3.2" |
| Net Weight (Lbs) | 11.7 |



| PACKAGING | | UPC | DIMENSIONS (LxWxH) | GROSS WEIGHT (Lbs) |
|-------------------|--------------|--------------|---------------------------|--------------------|
| Master Carton | 1 | 899645001080 | 18.1" x 18.1" x 6.1" | 14.3 |
| Country of Origin | China | | | |
| HS Tariff | 9405.11.6020 | | | |

ORDERING

| ITEM# | DESCRIPTION | CASE |
|-------------------|--|------|
| LVEX60 | LED VERSA-TOP™/18-30-50-60W/30-40-50K/120-277V/BLK | 1 |
| Manufactured by F | P.Q.L., Inc Manufacturer Model # SSDPT-60W-CCT-D-M-18, SSDPT-30W-CCT-D-M, SSDPT-50W-CCT-D-M, SSDPT-60W-CCT-D-M | |
| ACCESSORIES | | |
| LVEONE | SINGLE ARM BRACKET FOR VERSA-TOP™/BLK | 5 |
| LVETW0 | DOUBLE ARM BRACKET FOR VERSA-TOP™/BLK | 5 |
| LVETEN | SLIP FITTER BRACKET FOR VERSA-TOP™/BLK | 15 |
| LVECEL | CEILING BRACKET FOR VERSA-TOP™/BLK | 10 |
| LVEWP | STRAIGHT ARM BRACKET FOR VERSA-TOP™/BLK | 10 |
| LVECON | CONDUIT BRACKET FOR VERSA-TOP™/BLK | 30 |
| REPLACEMEN | T PARTS | |
| WP-CLB-60U | REPLACEMENT LED DRIVER | 1 |

BRACKET OPTIONS:







LVEX60+LVECEL







LVEX60+LVECON