



LF0606 LT. COMMERCIAL • 5YR LED LOW PROFILE CANOPY

FUEL PUMP CANOPY LUMINAIRES

FEATURES

- Thin low-profile design.
- Easy surface mounting.

APPLICATION

Ideal for retrofitting inefficient outdoor fixtures.

ELECTRICAL

Wattage	75W		
Voltage	100-277V		
Current	0.75A		
Power Factor	0.9		
Total Harmonic Distortion (THD)	15		
LIGHTING PERFORMANCE			
Lumens	9300		
Lumens Per Watt (Lm/W)	124		
Color Temperature (CCT)	5000K		
Color Rendering (CRI)	80		
R9 (Red Value)	8		
R13 (Skin Tones)	83		
Beam Angle	110°		
Light Distribution	Type VS		
BUG Rating (Backlight, Uplight, and Glare)	B3 - U3 - G1		
Dimmable Lighting Control	Dimmable 0-10V, Range 10% - 100%		
ENVIRONMENT			
Operating Temperature	-22° ~ 122°F		
Suitable Location	WET		
Ingress Protection Rating	IP65		
LIFESPAN			
Average Life (Hours)	50,000		
Warranty (Years)	5		
COMPONENTS			
LED Light Source	Samsung 2835		
Driver	Sosen SS-100E-58B		
CONSTRUCTION			
Housing	Aluminum		
Lens	Tempered Glass		
Base / Power Supply	Hard Wire		
Finish	White		
QUALIFICATIONS			
Manufacturer Model #	90004		
MINTERFER DE LA COMPANION DE L			



Manufactured by P.Q.L., Inc. · Published lumens on LED products are approximate and may vary slightly. · Specifications are subject to change without notice.


LF0606 LT. COMMERCIAL • 5YR LED LOW PROFILE CANOPY



DIMENSIONS (Inches)

Length	15"
Width/Diameter	15"
Height	2.7"
Weight (Lbs)	10

Line drawings may not be to scale and are for general reference only.



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	1	811768024982	17.4" x 16.5" x 16.5"	12.6
Country of Origin	China			
HS Tariff	9405.10.6020			

ORDERING

ITEM#	DESCRIPTION	CASE
LF0606	LED LOW PROFILE CANOPY 75W/50K/100-277V/DIMMABLE	1

Manufactured by P.Q.L., Inc. - Manufacturer Model # 90004

ADDITIONAL INFORMATION:

Note: To prevent water damage which may shorten the life of an exterior mounted fixture; the fixture should be properly weather sealed according to the installation instructions or between the fixture base and mounting surface. Damage due to improper installation may void the warranty.